

TYRES

Product group	Tyres
Item number	15285400
Valid tyre size	400 / 70 R 18
LI / SI / PR	147 A8 / 147 B
TL/TT	TL
Brand	Alliance
Tread pattern	585





Notes and features

- The Alliance 585 was developed for telehandlers, backhoe and compact loaders.
- It is suitable for use in agriculture as well as on construction sites.
- The large, non-directional tread pattern provides good traction and great performance even on hard surfaces.
- The high tread depth guarantees a long tyre life and good protection against tyre damage.



Technical Informations

Item number	15285400
EAN	8903635029571
Valid tyre size	400 / 70 R 18
Alternative size 1	16.0/70R18
LI / SI / PR	147 A8 / 147 B
TL/TT	TL
Brand	Alliance
Tread pattern	585
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	63,40
Recommended rim size	13
Permitted rim size	12, 12SDC, 13.00
Maximum air pressure [bar].	4,00
Section width (mm)	404
Outer diameter of tyre [mm].	1017
Stat. radius (SLR) [mm]	461
Rolling circumference [mm].	3026
Tread depth (mm)	30,0
Number of lugs	22x2
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
147 A8	3075	40		4,00	
147 B	3075	50		4,00	