

## TYRES

Product group	Tyres
Item number	15285420
Valid tyre size	400 / 70 R 20
LI / SI / PR	149 A8 / 149 B
TL/TT	TL
Brand	Alliance
Tread pattern	585



## Notes and features

- The Alliance 585 was developed for telehandlers, backhoe and compact loaders.
- It is suitable for use in agriculture as well as on construction sites.
- The large, non-directional tread pattern provides good traction and great performance even on hard surfaces.
- The high tread depth guarantees a long tyre life and good protection against tyre damage.

## Technical Informations

Item number	15285420
EAN	8903635029175
Valid tyre size	400 / 70 R 20
Alternative size 1	16.0/70R20
LI / SI / PR	149 A8 / 149 B
TL/TT	TL
Brand	Alliance
Tread pattern	585
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	70,40
Recommended rim size	W13
Permitted rim size	W12, 12SDC, 13SDC, W14L
Maximum air pressure [bar].	4,00
Section width (mm)	404
Outer diameter of tyre [mm].	1067
Stat. radius (SLR) [mm]	485
Rolling circumference [mm].	3237
Tread depth (mm)	30,0
Number of lugs	22x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A8	3250	40		4,00	
149 B	3250	50		4,00	