

TYRES

Product group	Tyres	
Item number	15710110	
Valid tyre size	AT 25 x 13 - 9	
LI / SI / PR	54 F, 4 PR	
TL/TT	TL	
Brand	BKT	
Tread pattern	AT 108	





Notes and features

- ATV traction tread
- Good grip even on unpaved terrain

• Protection against punctures due to special casing



Technical Informations

Item number	15710110
EAN	8903094000494
Valid tyre size	AT 25 x 13 - 9
LI / SI / PR	54 F, 4 PR
TL/TT	TL
Brand	BKT
Tread pattern	AT 108
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 75
Nettogewicht [kg] (gültig)	12,14
Recommended rim size	10.5
Permitted rim size	10.0
Maximum air pressure [bar].	0,35
Section width (mm)	320
Outer diameter of tyre [mm].	635
Tread depth (mm)	16,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
54 F	212	80		0,35	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.