

TYRES

Product group	Tyres
Item number	15710230
Valid tyre size	24 x 12 - 12
LI / SI / PR	95 A6, 4 PR
TL/TT	TL
Brand	BKT
Tread pattern	AT 316



Bohnenkamp
■ ■ ■ Moving Professionals



Notes and features

- The BKT AT 316 is a small agricultural tyre suitable for compact tractors in municipal work and maintenance
- Its tread pattern provides excellent traction and outstanding soil protection at the same time

Technical Informations

Item number	15710230
EAN	8903094001200
Valid tyre size	24 x 12 - 12
LI / SI / PR	95 A6, 4 PR
TL/TT	TL
Brand	BKT
Tread pattern	AT 316
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	10,44
Recommended rim size	10.50I-55, 10.50I-70, 10.50I-90
Permitted rim size	10.5
Maximum air pressure [bar].	1,40
Section width (mm)	315
Outer diameter of tyre [mm].	610
Stat. radius (SLR) [mm]	271
Rolling circumference [mm].	1769
Tread depth (mm)	12,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
95 A6	690	30		1,40	