

TYRES

Product group	Tyres	
Item number	15710384	
Valid tyre size	16 x 6.50 - 8	
LI / SI / PR	72 A3 / 68 A6, 6 PR	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	LG 306	



Notes and features

- Turf tyre with excellent contact area for low soil compaction.
- Rounded tyre shoulder for optimal turf protection.
- High tread pattern depth in conjunction with a rugged carcass for high mileage and protection against damage (punctures).



Technical Informations

Item number	15710384
EAN	8903094012367
Valid tyre size	16 x 6.50 - 8
LI / SI / PR	72 A3 / 68 A6, 6 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	LG 306
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	3,12
Recommended rim size	5.375
Maximum air pressure [bar].	2,90
Section width (mm)	170
Outer diameter of tyre [mm].	408
Stat. radius (SLR) [mm]	182
Rolling circumference [mm].	1183
Tread depth (mm)	7,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
72 A3	355	15		2,90	
68 A6	315	30		2,90	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.