Bohnenkamp Moving Professionals

19.09.2024

TYRES

Product group	Tyres	
Item number	15710393	
Valid tyre size	18 x 8.50 - 8	
LI / SI / PR	73 A3 / 70 A6, 4 PR	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	TR 317	



Notes and features

- Small tyre with agricultural tread pattern for lawn tractors and other landscape maintenance machinery.
- Offers good traction on loose subsoil.

• Low ground pressure also enables driving on delicate subsoils.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15710393
EAN	8903094038879
Valid tyre size	18 x 8.50 - 8
LI / SI / PR	73 A3 / 70 A6, 4 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	TR 317
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	5,50
Recommended rim size	7.00
Maximum air pressure [bar].	1,50
Section width (mm)	215
Outer diameter of tyre [mm].	450
Stat. radius (SLR) [mm]	198
Rolling circumference [mm].	1305
Tread depth (mm)	14,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
73 A3	365	15		1,50	
70 A6	335	30		1,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.