

## **TYRES**

Product group	Tyres	
Item number	15710396	
Valid tyre size	18 x 8.50 - 8	
LI / SI / PR	PR 82 A3 / 78 A6, 6 PR	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	LG 306	



## **Notes and features**

- Turf tyre with excellent contact area for low soil compaction.
- Rounded tyre shoulder for optimal turf protection.
- High tread pattern depth in conjunction with a rugged carcass for high mileage and protection against damage (punctures).



## **Technical Informations**

Item number	15710396
EAN	8903094012381
Valid tyre size	18 x 8.50 - 8
LI / SI / PR	82 A3 / 78 A6, 6 PR
TL/TT	TL
Brand	BKT
Tread pattern	LG 306
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	4,85
Recommended rim size	7.001
Maximum air pressure [bar].	2,30
Section width (mm)	215
Outer diameter of tyre [mm].	450
Stat. radius (SLR) [mm]	204
Rolling circumference [mm].	1346
Tread depth (mm)	8,0
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
82 A3	475	15		2,30	
78 A6	425	30		2,30	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.