

TYRES

Product group	Tyres
Item number	15710420
Valid tyre size	20 x 10.00 - 8
LI / SI / PR	94 A3 / 90 A6, 6 PR
TL/TT	TL
Brand	BKT
Tread pattern	LG 306



Notes and features

- Turf tyre with excellent contact area for low soil compaction.
- Rounded tyre shoulder for optimal turf protection.
- High tread pattern depth in conjunction with a rugged carcass for high mileage and protection against damage (punctures).

Technical Informations

Item number	15710420
EAN	8903094012497
Valid tyre size	20 x 10.00 - 8
LI / SI / PR	94 A3 / 90 A6, 6 PR
TL/TT	TL
Brand	BKT
Tread pattern	LG 306
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	6,14
Recommended rim size	8.00I
Permitted rim size	7.00I
Maximum air pressure [bar].	2,20
Section width (mm)	254
Outer diameter of tyre [mm].	508
Stat. radius (SLR) [mm]	221
Rolling circumference [mm].	1473
Tread depth (mm)	8,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
94 A3	670	15		2,20	
90 A6	600	30		2,20	