

## **TYRES**

Product group	Tyres	
Item number	15710480	
Valid tyre size	23 x 8.50 - 12	
LI / SI / PR	89 A6, 6 PR	
TL/TT	TL	
Brand	BKT	
Tread pattern	LG 306	



## Notes and features

- Turf tyre with excellent contact area for low soil compaction.
- Rounded tyre shoulder for optimal turf protection.
- High tread pattern depth in conjunction with a rugged carcass for high mileage and protection against damage (punctures).



## **Technical Informations**

Item number	15710480
EAN	8903094012602
Valid tyre size	23 x 8.50 - 12
LI / SI / PR	89 A6, 6 PR
TL/TT	TL
Brand	BKT
Tread pattern	LG 306
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	7,76
Recommended rim size	7.001
Permitted rim size	7JA
Maximum air pressure [bar].	2,30
Section width (mm)	210
Outer diameter of tyre [mm].	575
Stat. radius (SLR) [mm]	258
Rolling circumference [mm].	1709
Tread depth (mm)	10,0
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
89 A6	580	30		2,30	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.