

TYRES

Product group	Tyres	
Item number	15710485	
Valid tyre size	23 x 8.50 - 12	
LI / SI / PR	89 A6, 6 PR	
TL/TT	TL	
Brand	BKT	
Tread pattern	TR 315	





Notes and features

• Excellent traction.

 Resistant rubber compound protects against punctures for longer durability.



Technical Informations

Item number	15710485
EAN	8903094022359
Valid tyre size	23 x 8.50 - 12
LI / SI / PR	89 A6, 6 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 315
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	6,95
Recommended rim size	7JA
Permitted rim size	7.00, 7.001
Maximum air pressure [bar].	2,30
Section width (mm)	205
Outer diameter of tyre [mm].	575
Stat. radius (SLR) [mm]	258
Rolling circumference [mm].	1668
Tread depth (mm)	13,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
89 A6	580	30		2,30	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.