

TYRES

Product group	Tyres	
Item number	15710495	
Valid tyre size	23 x 10.50 - 12	
LI / SI / PR	96 A6, 6 PR	
TL/TT	TL	
Brand	BKT	
Tread pattern	TR 315	





Notes and features

• Excellent traction.

 Resistant rubber compound protects against punctures for longer durability.



Technical Informations

Item number	15710495
EAN	8903094022311
Valid tyre size	23 x 10.50 - 12
LI / SI / PR	96 A6, 6 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 315
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	9.54
Recommended rim size	8.50 JA
Permitted rim size	7 JA, 7.00 I, 8.50 I
Maximum air pressure [bar].	2,20
Section width (mm)	255
Outer diameter of tyre [mm].	600
Stat. radius (SLR) [mm]	272
Rolling circumference [mm].	1840
Tread depth (mm)	15,5
Number of lugs	15x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
96 A6	710	30		2,20	
	800	15		2,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.