

TYRES

Product group	Tyres	
Item number	15710496	
Valid tyre size	24 x 13.00 - 12	
LI / SI / PR	107 A6, 6 PR	
TL/TT	TL	
Brand	BKT	
Tread pattern	LG 408	





Notes and features

- Wide tyre with surface tread pattern for good traction.
- Especially gentle on the lawn.



Technical Informations

Item number	15710496
EAN	8903094012879
Valid tyre size	24 x 13.00 - 12
LI / SI / PR	107 A6, 6 PR
TL/TT	TL
Brand	BKT
Tread pattern	LG 408
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	12,47
Recommended rim size	10.5I-55, 10.5I-70, 10.5I-90
Permitted rim size	10.5
Maximum air pressure [bar].	2,20
Section width (mm)	320
Outer diameter of tyre [mm].	605
Stat. radius (SLR) [mm]	269
Rolling circumference [mm].	1755
Tread depth (mm)	8,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
107 A6	975	30		2,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.