

TYRES

Product group	Tyres
Item number	15710501
Valid tyre size	26 x 12.00 - 12
LI / SI / PR	124 A3 / 121 A6, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	LG 306



Notes and features

- Turf tyre with excellent contact area for low soil compaction.
- Rounded tyre shoulder for optimal turf protection.
- High tread pattern depth in conjunction with a rugged carcass for high mileage and protection against damage (punctures).

Technical Informations

Item number	15710501
EAN	8903094012695
Valid tyre size	26 x 12.00 - 12
LI / SI / PR	124 A3 / 121 A6, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	LG 306
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	15,92
Recommended rim size	10.50I
Permitted rim size	10JA, 8JA
Maximum air pressure [bar].	4,50
Section width (mm)	310
Outer diameter of tyre [mm].	640
Stat. radius (SLR) [mm]	283
Rolling circumference [mm].	1856
Tread depth (mm)	10,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
124 A3	1600	15		4,50	
121 A6	1450	30		4,50	