

TYRES

Product group	Tyres	
Item number	15710502	
Valid tyre size	26 x 12.00 - 12	
LI / SI / PR	123 A6, 14 PR	
TL/TT	TL	
Brand	BKT	
Tread pattern	LG 306	



Notes and features

- Turf tyre with excellent contact area for low soil compaction.
- Rounded tyre shoulder for optimal turf protection.
- High tread pattern depth in conjunction with a rugged carcass for high mileage and protection against damage (punctures).



Technical Informations

Item number	15710502
EAN	8903094012718
Valid tyre size	26 x 12.00 - 12
LI / SI / PR	123 A6, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	LG 306
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	15,92
Recommended rim size	10.501
Permitted rim size	10.50JA, 8.50JA
Maximum air pressure [bar].	5,20
Section width (mm)	310
Outer diameter of tyre [mm].	640
Stat. radius (SLR) [mm]	283
Rolling circumference [mm].	1945
Tread depth (mm)	10,2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
123 A6	1550	30		5,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.