

TYRES

| | |
|-----------------|-----------------|
| Product group | Tyres |
| Item number | 15710507 |
| Valid tyre size | 26 x 12.00 - 12 |
| LI / SI / PR | 112 A6, 8 PR |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | AS 504 |



Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

Technical Informations

| | |
|------------------------------|-----------------------|
| Item number | 15710507 |
| EAN | 8903094060863 |
| Valid tyre size | 26 x 12.00 - 12 |
| LI / SI / PR | 112 A6, 8 PR |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | AS 504 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 18,26 |
| Recommended rim size | AT10.50 |
| Permitted rim size | 8.0, 8.5, 9.0, 10.50I |
| Maximum air pressure [bar]. | 3,00 |
| Section width (mm) | 310 |
| Outer diameter of tyre [mm]. | 648 |
| Stat. radius (SLR) [mm] | 298 |
| Rolling circumference [mm]. | 1932 |
| Tread depth (mm) | 16,5 |
| Number of lugs | 15x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 112 A6 | 1120 | 30 | | 3,00 | |