

TYRES

Product group	Tyres	
Item number	15710515	
Valid tyre size	26 x 12.00 - 12	
LI / SI / PR	116 A3 / 112 A6, 8 PR	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	TR 315	





Notes and features

• Excellent traction.

 Resistant rubber compound protects against punctures for longer durability.



Technical Informations

Item number	15710515
EAN	8903094022410
Valid tyre size	26 x 12.00 - 12
LI / SI / PR	116 A3 / 112 A6, 8 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	TR 315
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	14,19
Recommended rim size	10.5JA
Permitted rim size	8.5JA, 9.5JA
Maximum air pressure [bar].	3,00
Section width (mm)	308
Outer diameter of tyre [mm].	655
Stat. radius (SLR) [mm]	289
Rolling circumference [mm].	1905
Tread depth (mm)	19,0
Number of lugs	20x2
Lug width (mm)	14
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
116 A3	1250	15		3,00	
112 A6	1120	30		3,00	