

TYRES

Product group	Tyres
Item number	15710520
Valid tyre size	26 x 12.00 - 12
LI / SI / PR	121 A6, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 315



Bohnenkamp
Moving Professionals



Notes and features

- Excellent traction.
- Resistant rubber compound protects against punctures for longer durability.

Technical Informations

Item number	15710520
EAN	8903094022397
Valid tyre size	26 x 12.00 - 12
LI / SI / PR	121 A6, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 315
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	15,33
Recommended rim size	10.50JA
Permitted rim size	8.50JA, 9.50JA
Maximum air pressure [bar].	4,50
Section width (mm)	308
Outer diameter of tyre [mm].	655
Stat. radius (SLR) [mm]	289
Rolling circumference [mm].	1905
Tread depth (mm)	18,5
Number of lugs	20x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
121 A6	1450	30		4,50	