Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	er 15710545	
Valid tyre size	27 x 10.50 - 15	
LI / SI / PR	90 A3 / 87 A6, 4 PR	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	LG 306	



Notes and features

- Turf tyre with excellent contact area for low soil compaction.
- Rounded tyre shoulder for optimal turf protection.
- High tread pattern depth in conjunction with a rugged carcass for high mileage and protection against damage (punctures).

Bohnenkamp Moving Professionals

Technical Informations

Item number 15710545 EAN 8903094029822	
EAN 8903094029822	
Valid tyre size 27 x 10.50 - 15	
LI/SI/PR 90 A3 / 87 A6, 4 PR	
TL/TT TL	
Brand BKT	
Tread pattern LG 306	
Antistatic No	
Tyre colour Black	
ECE regulation number ECE 106	
Nettogewicht [kg] (gültig) 13,45	
Recommended rim size 8.00LB	
Maximum air pressure [bar]. 2,10	
Section width (mm) 272	
Outer diameter of tyre [mm]. 705	
Stat. radius (SLR) [mm] 318	
Rolling circumference [mm]. 2042	
Tread depth (mm) 9,0	
E-Ready No	

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
90 A3	600	15		2,10	
87 A6	545	30		2,10	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.