

TYRES

Product group	Tyres
Item number	15710551
Valid tyre size	29 x 12.50 - 15
LI / SI / PR	106 B, 8 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 319





Notes and features

- The BKT TR 319 is an implement tyre for orchard harvesters, trenchers in horticulture and soil tillage equipment.
- The large contact area enables good traction.
- The tyre is very suitable for use on wet and dry surfaces.



Technical Informations

Item number	15710551
EAN	8903094053247
Valid tyre size	29 x 12.50 - 15
LI / SI / PR	106 B, 8 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 319
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	22,20
Recommended rim size	10LB
Maximum air pressure [bar].	3,10
Section width (mm)	312
Outer diameter of tyre [mm].	755
Stat. radius (SLR) [mm]	360
Rolling circumference [mm].	2264
Tread depth (mm)	19,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
106 B	950	50		3,10	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.