

TYRES

Product group	Tyres	
Item number	15710552	
Valid tyre size	31 x 15.50 - 15	
LI / SI / PR	116 B, 8 PR	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	TR 313	





Notes and features

• Excellent traction.

 Resistant rubber compound protects against punctures for longer durability.



Technical Informations

Item number	15710552
EAN	8903094025589
Valid tyre size	31 x 15.50 - 15
LI / SI / PR	116 B, 8 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 313
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	25,40
Recommended rim size	13LB
Maximum air pressure [bar].	3,10
Section width (mm)	370
Outer diameter of tyre [mm].	780
Stat. radius (SLR) [mm]	342
Rolling circumference [mm].	2233
Tread depth (mm)	23,5
Number of lugs	19x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
116 B	1250	50		3,10	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.