

TYRES

Product group	Tyres	
Item number	15710555	
Valid tyre size	31 x 15.50 - 15	
LI / SI / PR	121 B, 10 PR	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	TR 315	





Notes and features

• Excellent traction.

 Resistant rubber compound protects against punctures for longer durability.



Technical Informations

Item number	15710555
EAN	8903094043774
Valid tyre size	31 x 15.50 - 15
LI / SI / PR	121 B, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 315
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	30,88
Recommended rim size	13LB
Permitted rim size	13.00
Maximum air pressure [bar].	4,10
Section width (mm)	390
Outer diameter of tyre [mm].	800
Stat. radius (SLR) [mm]	354
Rolling circumference [mm].	2320
Tread depth (mm)	20,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
121 B	1450	50		4,10	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.