

TYRES

Product group	Tyres
Item number	15710577
Valid tyre size	33 x 15.50 - 16.5
LI / SI / PR	125 A3 / 121 A6, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	LG 306



Notes and features

- Turf tyre with excellent contact area for low soil compaction.
- Rounded tyre shoulder for optimal turf protection.
- High tread pattern depth in conjunction with a rugged carcass for high mileage and protection against damage (punctures).

Technical Informations

Item number	15710577
EAN	8903094037100
Valid tyre size	33 x 15.50 - 16.5
LI / SI / PR	125 A3 / 121 A6, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	LG 306
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	37,39
Recommended rim size	12.00
Permitted rim size	11.00, 13.00
Maximum air pressure [bar].	2,10
Section width (mm)	396
Outer diameter of tyre [mm].	840
Stat. radius (SLR) [mm]	374
Rolling circumference [mm].	2495
Tread depth (mm)	14,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
125 A3	1650	15		2,10	
121 A6	1450	30		2,10	