

TYRES

Product group	Tyres
Item number	15710630
Valid tyre size	44 x 18.00 - 20
LI / SI / PR	122 A3 / 119 A6, 4 PR
TL/TT	TL
Brand	BKT
Tread pattern	LG 306



Notes and features

- Turf tyre with excellent contact area for low soil compaction.
- Rounded tyre shoulder for optimal turf protection.
- High tread pattern depth in conjunction with a rugged carcass for high mileage and protection against damage (punctures).

Technical Informations

Item number	15710630
EAN	8903094030231
Valid tyre size	44 x 18.00 - 20
LI / SI / PR	122 A3 / 119 A6, 4 PR
TL/TT	TL
Brand	BKT
Tread pattern	LG 306
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	62,14
Recommended rim size	W14L
Permitted rim size	W14LH
Maximum air pressure [bar].	1,40
Section width (mm)	475
Outer diameter of tyre [mm].	1180
Stat. radius (SLR) [mm]	518
Rolling circumference [mm].	3471
Tread depth (mm)	20,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
122 A3	1500	15		1,40	
119 A6	1360	30		1,40	