Bohnenkamp Moving Professionals

16.11.2024

TYRES

Product group	Tyres
Item number	15710660
Valid tyre size	48 x 31 - 20
LI / SI / PR	148 B, 12 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	Flotation 351





Notes and features

- High flotation tyre with tractor tread pattern
- Extra deep tread pattern for excellent traction and a long service life
- Wide base tyre characteristics for high load capacities, even with low inflation pressures
- Ideally suited for damp or wet ground

Bohnenkamp Moving Professionals

Technical Informations

Item number	15710660
EAN	8903094026135
Valid tyre size	48 x 31 - 20
LI / SI / PR	148 B, 12 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	Flotation 351
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	176,53
Recommended rim size	26.00HF
Maximum air pressure [bar].	2,70
Section width (mm)	775
Outer diameter of tyre [mm].	1283
Stat. radius (SLR) [mm]	559
Rolling circumference [mm].	3886
Tread depth (mm)	47,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 B	3150	50		2,70	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.