

TYRES

Product group	Tyres	
Item number	15711240	
Valid tyre size	18 x 8.50 - 8	
LI / SI / PR	85 A8, 6 PR	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	Rib 774 (A)	





Notes and features

- The BKT RIB 774 (A) is a tyre for various towed agricultural implements.
- The tyre provides high loading capacities and low soil compaction at the same time.
- When used for road transport, the fine grooved tread pattern ensures low rolling resistance.



Technical Informations

Item number	15711240
EAN	8903094056910
Valid tyre size	18 x 8.50 - 8
LI / SI / PR	85 A8, 6 PR
TL/TT	TL
Brand	BKT
Tread pattern	Rib 774 (A)
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	6,34
Recommended rim size	7.00
Maximum air pressure [bar].	3,00
Section width (mm)	225
Outer diameter of tyre [mm].	460
Stat. radius (SLR) [mm]	217
Rolling circumference [mm].	1390
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
85 A8	515	40		3,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.