Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	15711260	
Valid tyre size	5.00 - 12	
LI / SI / PR	67 A6 / 63 A8, 6 PR	
TL/TT	TT	
Brand	ВКТ	
Tread pattern	TR 171	



Notes and features

- Suitable for wet surfaces. .
- Extra high lugs for long service life.

Very good traction and self-cleaning. •

Bohnenkamp Moving Professionals

Technical Informations

Item number	15711260	
EAN	8903094033553	
Valid tyre size	5.00 - 12	
LI / SI / PR	67 A6 / 63 A8, 6 PR	
TL/TT	Π	
Brand	ВКТ	
Tread pattern	TR 171	
Antistatic	No	
Tyre colour	Black	
ECE regulation number	ECE 106	
Nettogewicht [kg] (gültig)	6,63	
Recommended rim size	3.00D	
Permitted rim size	3.00DT, 3.00D, 4JA, 3.50B	
Maximum air pressure [bar].	2,80	
Section width (mm)	130	
Outer diameter of tyre [mm].	580	
Stat. radius (SLR) [mm]	272	
Rolling circumference [mm].	1750	
Tread depth (mm)	27,0	
Number of lugs	13x2	
E-Ready	No	

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
67 A6	307	30		2,80	
63 A8	272	40		2,80	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.