

TYRES

Product group	Tyres
Item number	15711280
Valid tyre size	6.5 / 80 - 12
LI / SI / PR	80 A8 / 93 A8, 6 PR
TL/TT	TT
Brand	BKT
Tread pattern	AS 504



Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

Technical Informations

Item number	15711280
EAN	8903094019205
Valid tyre size	6.5 / 80 - 12
LI / SI / PR	80 A8 / 93 A8, 6 PR
TL/TT	TT
Brand	BKT
Tread pattern	AS 504
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	7,54
Recommended rim size	5J
Permitted rim size	4.25, 5JA, 5.00
Maximum air pressure [bar].	3,60
Section width (mm)	163
Outer diameter of tyre [mm].	608
Stat. radius (SLR) [mm]	273
Rolling circumference [mm].	1851
Tread depth (mm)	14,5
Number of lugs	16x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
80 A8	450	40	Drive Wheel	3,60	LLV
93 A8	650	40	Free Rolling	3,60	LLV