

## TYRES

Product group	Tyres
Item number	15711305
Valid tyre size	7.00 - 12
LI / SI / PR	83 A8 / 95 A8, 6 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504



Bohnenkamp  
Moving Professionals



## Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

## Technical Informations

Item number	15711305
EAN	8903094019274
Valid tyre size	7.00 - 12
LI / SI / PR	83 A8 / 95 A8, 6 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	12,17
Recommended rim size	4.5
Permitted rim size	4.5J, 4.25J, 4J
Maximum air pressure [bar].	3,40
Section width (mm)	187
Outer diameter of tyre [mm].	683
Stat. radius (SLR) [mm]	300
Rolling circumference [mm].	2001
Tread depth (mm)	19,0
Number of lugs	22x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
83 A8	487	40	Drive Wheel	3,40	LLV
95 A8	690	40	Free Rolling	3,40	LLV