Bohnenkamp Moving Professionals

15.11.2024

TYRES

| Product group | Tyres |
|-----------------|---------------|
| Item number | 15711310 |
| Valid tyre size | 300 / 65 - 12 |
| LI / SI / PR | 116 A8, 8 PR |
| TL/TT | TL |
| Brand | ВКТ |
| Tread pattern | Rib 775 |



Notes and features

• Fine, soil-protecting tread pattern.

• Minimal rolling resistance.

Bohnenkamp Moving Professionals

Technical Informations

| Item number | 15711310 |
|------------------------------|---------------|
| EAN | 8903094011049 |
| Valid tyre size | 300 / 65 - 12 |
| LI / SI / PR | 116 A8, 8 PR |
| TL/TT | ΤL |
| Brand | ВКТ |
| Tread pattern | Rib 775 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 23,47 |
| Recommended rim size | 9.0 |
| Maximum air pressure [bar]. | 2,60 |
| Section width (mm) | 305 |
| Outer diameter of tyre [mm]. | 685 |
| Stat. radius (SLR) [mm] | 304 |
| Rolling circumference [mm]. | 2007 |
| Tread depth (mm) | 10,0 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 116 A8 | 1250 | 40 | Free Rolling | 2,60 | LLV |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.