

TYRES

Product group	Tyres
Item number	15711540
Valid tyre size	10.0 / 80 - 12
LI / SI / PR	121 A8, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 702



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction
- Good handling characteristics, both on the road and in the field

Technical Informations

Item number	15711540
EAN	8903094009176
Valid tyre size	10.0 / 80 - 12
LI / SI / PR	121 A8, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 702
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	15,11
Recommended rim size	9.00
Permitted rim size	7.0
Maximum air pressure [bar].	3,90
Section width (mm)	264
Outer diameter of tyre [mm].	710
Stat. radius (SLR) [mm]	317
Rolling circumference [mm].	2144
Tread depth (mm)	10,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
121 A8	1450	40	Free Rolling	3,90	LLV
	1000	40	Drive Wheel	3,90	LLV