

TYRES

Product group	Tyres	
Item number	15711545	
Valid tyre size	10.0 / 80 - 12	
LI / SI / PR	117 A6 / 110 A8, 6 PR	
TL/TT	TL	
Brand	BKT	
Tread pattern	Rib Implement (A)	



Notes and features

• Fine, soil-protecting tread pattern.

• Minimal rolling resistance.



Technical Informations

Item number	15711545
EAN	8903094010868
Valid tyre size	10.0 / 80 - 12
LI / SI / PR	117 A6 / 110 A8, 6 PR
TL/TT	TL
Brand	BKT
Tread pattern	Rib Implement (A)
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	17,62
Recommended rim size	9.0
Permitted rim size	7.0
Maximum air pressure [bar].	2,30
Section width (mm)	264
Outer diameter of tyre [mm].	746
Stat. radius (SLR) [mm]	329
Rolling circumference [mm].	2186
Tread depth (mm)	18,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
117 A6	1285	30		3,20	
110 A8	1060	40		3,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.