

TYRES

| | |
|-----------------|--------------|
| Product group | Tyres |
| Item number | 15711590 |
| Valid tyre size | 9.00 - 13 |
| LI / SI / PR | 116 A8, 8 PR |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Sand Star |



Bohnenkamp
Moving Professionals



Notes and features

- The BKT Sand Star was specially developed for trailers and agricultural machines like sprayers, balers, ploughs etc.
- Its block tread pattern provides very good traction and optimum ground contact on loose and sandy surfaces and ensures reduced soil compaction.
- The rubber compound is best suited for extreme weather conditions.

Technical Informations

| | |
|------------------------------|---------------|
| Item number | 15711590 |
| EAN | 8903094031757 |
| Valid tyre size | 9.00 - 13 |
| LI / SI / PR | 116 A8, 8 PR |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Sand Star |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 16,83 |
| Recommended rim size | 5.50F |
| Permitted rim size | 5.50WB |
| Maximum air pressure [bar]. | 2,75 |
| Section width (mm) | 245 |
| Outer diameter of tyre [mm]. | 784 |
| Stat. radius (SLR) [mm] | 342 |
| Rolling circumference [mm]. | 2297 |
| Tread depth (mm) | 7,0 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 116 A8 | 1250 | 40 | | 2,75 | |