

TYRES

Product group	Tyres
Item number	15711633
Valid tyre size	7 - 14
LI / SI / PR	72 A6 / 68 A8, 4 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 126



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Suitable for smaller tractors.
- High lugs offer good traction on wet ground.

Technical Informations

Item number	15711633
EAN	8903094004539
Valid tyre size	7 - 14
LI / SI / PR	72 A6 / 68 A8, 4 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 126
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	10,02
Recommended rim size	5JA
Permitted rim size	5KB
Maximum air pressure [bar].	1,60
Section width (mm)	170
Outer diameter of tyre [mm].	690
Stat. radius (SLR) [mm]	320
Rolling circumference [mm].	2070
Tread depth (mm)	27,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
72 A6	355	30		1,60	
68 A8	315	40		1,60	