

TYRES

| | |
|-----------------|-----------------|
| Product group | Tyres |
| Item number | 15711650 |
| Valid tyre size | 200 / 60 - 14.5 |
| LI / SI / PR | 106 A8, 10 PR |
| TL/TT | TT |
| Brand | BKT |
| Tread pattern | Rib 774 (A) |



Notes and features

- The BKT RIB 774 (A) is a tyre for various towed agricultural implements.
- The tyre provides high loading capacities and low soil compaction at the same time.
- When used for road transport, the fine grooved tread pattern ensures low rolling resistance.

Technical Informations

| | |
|------------------------------|-----------------|
| Item number | 15711650 |
| EAN | 8903094010974 |
| Valid tyre size | 200 / 60 - 14.5 |
| LI / SI / PR | 106 A8, 10 PR |
| TL/TT | TT |
| Brand | BKT |
| Tread pattern | Rib 774 (A) |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 11,78 |
| Recommended rim size | 6.75 |
| Maximum air pressure [bar]. | 5,00 |
| Section width (mm) | 210 |
| Outer diameter of tyre [mm]. | 610 |
| Stat. radius (SLR) [mm] | 278 |
| Rolling circumference [mm]. | 1785 |
| Tread depth (mm) | 10,0 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 106 A8 | 950 | 40 | Free Rolling | 5,00 | LLV |