

TYRES

Product group	Tyres
Item number	15711655
Valid tyre size	250 / 65 - 14.5
LI / SI / PR	124 A8, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	Rib 774 (A)



Notes and features

- The BKT RIB 774 (A) is a tyre for various towed agricultural implements.
- The tyre provides high loading capacities and low soil compaction at the same time.
- When used for road transport, the fine grooved tread pattern ensures low rolling resistance.

Technical Informations

Item number	15711655
EAN	8903094027255
Valid tyre size	250 / 65 - 14.5
LI / SI / PR	124 A8, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	Rib 774 (A)
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	17.80
Recommended rim size	8.00
Permitted rim size	6.75
Maximum air pressure [bar].	5,50
Section width (mm)	255
Outer diameter of tyre [mm].	675
Stat. radius (SLR) [mm]	303
Rolling circumference [mm].	1978
Tread depth (mm)	9,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
124 A8	1600	40	Free Rolling	5,50	LLV