

TYRES

Product group	Tyres	
Item number	15711676	
Valid tyre size	185 / 65 - 15	
LI / SI / PR	76 A8 / 89 A8, 4 PR	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	AS 507	





Notes and features

• For field and special operations

High traction



Technical Informations

Item number	15711676
EAN	8903094019489
Valid tyre size	185 / 65 - 15
LI / SI / PR	76 A8 / 89 A8, 4 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 507
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	9,81
Recommended rim size	5.5
Maximum air pressure [bar].	2,80
Section width (mm)	185
Outer diameter of tyre [mm].	640
Stat. radius (SLR) [mm]	301
Rolling circumference [mm].	1894
Tread depth (mm)	14,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
76 A8	400	40	Drive Wheel	2,80	LLV
85 A8	515	40	Free Rolling	2,80	LLV

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.