

## TYRES

Product group	Tyres
Item number	15711680
Valid tyre size	5.00 - 15
LI / SI / PR	75 A8 / 88 A8, 6 PR
TL/TT	TT
Brand	BKT
Tread pattern	AS 504



Bohnenkamp  
Moving Professionals



## Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

## Technical Informations

Item number	15711680
EAN	8903094019151
Valid tyre size	5.00 - 15
LI / SI / PR	75 A8 / 88 A8, 6 PR
TL/TT	TT
Brand	BKT
Tread pattern	AS 504
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	7,10
Recommended rim size	3.50D
Permitted rim size	3.00D, 4.00E, 4J
Maximum air pressure [bar].	3,50
Section width (mm)	140
Outer diameter of tyre [mm].	657
Stat. radius (SLR) [mm]	308
Rolling circumference [mm].	1957
Tread depth (mm)	16,0
Number of lugs	16x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
75 A8	387	40	Drive Wheel	3,50	LLV
88 A8	560	40	Free Rolling	3,50	LLV