

TYRES

Product group	Tyres
Item number	15711686
Valid tyre size	6.5 / 80 - 15
LI / SI / PR	92 A8 / 104 A8, 8 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 505



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- For field and special operations
- High traction

Technical Informations

Item number	15711686
EAN	8903094019472
Valid tyre size	6.5 / 80 - 15
LI / SI / PR	92 A8 / 104 A8, 8 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 505
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	10,92
Recommended rim size	5.00
Permitted rim size	4.50K, 5K, 5J
Maximum air pressure [bar].	4,80
Section width (mm)	169
Outer diameter of tyre [mm].	683
Stat. radius (SLR) [mm]	325
Rolling circumference [mm].	2106
Tread depth (mm)	19,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
92 A8	630	40	Drive Wheel	4,80	LLV
104 A8	900	40	Free Rolling	4,80	LLV