Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	15711689	
Valid tyre size	400 / 45 L - 17.5	
LI / SI / PR	156 A8, 14 PR	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	Terra Trax	





Notes and features

- The BKT Terra Trax was newly developed for feed mixers . and other agricultural vehicles and trailers.
- The tyre is characterised by its particularly wide tread • pattern and high loading capacities.
- Its large contact area and the special rubber compound • ensure slow wear and excellent durability.
- Thanks to the low rolling resistance, the tyre enables fuel • savings during transport on paved roads and other hard surfaces.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15711689
EAN	8903094063451
Valid tyre size	400 / 45 L - 17.5
LI / SI / PR	156 A8, 14 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	Terra Trax
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	45,49
Recommended rim size	14.00
Maximum air pressure [bar].	6,00
Section width (mm)	398
Outer diameter of tyre [mm].	785
Stat. radius (SLR) [mm]	361
Rolling circumference [mm].	2370
Tread depth (mm)	15,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 A8	4000	40		6,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.