

TYRES

Product group	Tyres
Item number	15711690
Valid tyre size	7.5L - 15
LI / SI / PR	100 A8 / 113 A8, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	AS 504



Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

Technical Informations

Item number	15711690
EAN	8903094019403
Valid tyre size	7.5L - 15
LI / SI / PR	100 A8 / 113 A8, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	AS 504
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	14,76
Recommended rim size	6LB
Permitted rim size	5K, 5.50J, 5.50K
Maximum air pressure [bar].	3,70
Section width (mm)	210
Outer diameter of tyre [mm].	765
Stat. radius (SLR) [mm]	354
Rolling circumference [mm].	2280
Tread depth (mm)	25,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
100 A8	800	40	Drive Wheel	3,70	LLV
113 A8	1150	40	Free Rolling	3,70	LLV