

TYRES

Product group	Tyres
Item number	15711694
Valid tyre size	31 X 13.50 - 15
LI / SI / PR	124 B, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation Rib Implement



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Flotation Rib Implement is a HF-1 tyre for agricultural implements and trailers
- It provides high flotation with minimal soil compaction and perfect ground pressure distribution
- The strong nylon casing as well as the cut-, chip- and wear-resistant rubber compound ensure a long service life for the tyre

Technical Informations

Item number	15711694
EAN	8903094040469
Valid tyre size	31 X 13.50 - 15
LI / SI / PR	124 B, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation Rib Implement
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	31,79
Recommended rim size	10
Maximum air pressure [bar].	5,20
Section width (mm)	360
Outer diameter of tyre [mm].	780
Stat. radius (SLR) [mm]	359
Rolling circumference [mm].	2129
Tread depth (mm)	9,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
124 B	1600	50	Free Rolling	5,20	