

TYRES

| | |
|-----------------|--------------------|
| Product group | Tyres |
| Item number | 15711695 |
| Valid tyre size | 9.5L - 15 SL |
| LI / SI / PR | 112 D, 8 PR |
| TL/TT | TT |
| Brand | BKT |
| Tread pattern | Farm Implement I-1 |



Notes and features

- The BKT Farm Implement I-1 is a universal implement tyre for road and field applications as well as for soil tillage operations
- As a high-speed tyre, it has speed index D and is approved up to 65 km/h
- Thanks to its excellent flotation capabilities, it reduces soil compaction and protects soil and crops

Technical Informations

| | |
|------------------------------|--------------------|
| Item number | 15711695 |
| EAN | 8903094006144 |
| Valid tyre size | 9.5L - 15 SL |
| LI / SI / PR | 112 D, 8 PR |
| TL/TT | TT |
| Brand | BKT |
| Tread pattern | Farm Implement I-1 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 13,12 |
| Recommended rim size | 7.00 |
| Permitted rim size | 8LB |
| Maximum air pressure [bar]. | 3,00 |
| Section width (mm) | 241 |
| Outer diameter of tyre [mm]. | 765 |
| Stat. radius (SLR) [mm] | 340 |
| Rolling circumference [mm]. | 2242 |
| Tread depth (mm) | 8,0 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 112 D | 1120 | 65 | | 3,00 | |