

TYRES

Product group	Tyres
Item number	15711708
Valid tyre size	7 - 16
LI / SI / PR	75 A6 / 71 A8, 4 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 144



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Agricultural bias tyre for smaller tractors.
- Wide lug spaces for good traction on wet surfaces.
- Angled lugs in the centre for better ride comfort.

Technical Informations

Item number	15711708
EAN	8903094004706
Valid tyre size	7 - 16
LI / SI / PR	75 A6 / 71 A8, 4 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 144
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	11,97
Recommended rim size	6LB
Permitted rim size	6.00F
Maximum air pressure [bar].	1,60
Section width (mm)	183
Outer diameter of tyre [mm].	740
Stat. radius (SLR) [mm]	344
Rolling circumference [mm].	2223
Tread depth (mm)	25,0
Number of lugs	15x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
75 A6	387	30		1,60	
71 A8	345	40		1,60	