

TYRES

Product group	Tyres
Item number	15711709
Valid tyre size	8 - 16
LI / SI / PR	91 A6 / 88 A8, 6 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 144



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Agricultural bias tyre for smaller tractors.
- Wide lug spaces for good traction on wet surfaces.
- Angled lugs in the centre for better ride comfort.

Technical Informations

Item number	15711709
EAN	8903094004720
Valid tyre size	8 - 16
LI / SI / PR	91 A6 / 88 A8, 6 PR
TL/TT	TT
Brand	BKT
Tread pattern	TR 144
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	14,88
Recommended rim size	6LB
Permitted rim size	6.00F
Maximum air pressure [bar].	1,90
Section width (mm)	200
Outer diameter of tyre [mm].	785
Stat. radius (SLR) [mm]	358
Rolling circumference [mm].	2342
Tread depth (mm)	27,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
91 A6	615	30		1,90	
88 A8	560	40		1,90	