

TYRES

Product group	Tyres
Item number	15711710
Valid tyre size	11 L - 16 SL
LI / SI / PR	116 A6, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	Industrial Rib F3





Notes and features

- Suitable for fields, roads and soil cultivation.
- Outstanding cut resistance.

• Long service life.



Technical Informations

Item number	15711710
EAN	8903094000142
Valid tyre size	11 L - 16 SL
LI / SI / PR	116 A6, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	Industrial Rib F3
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	23,69
Recommended rim size	W8L
Permitted rim size	8LB, 10LB, W10L
Maximum air pressure [bar].	3,60
Section width (mm)	279
Outer diameter of tyre [mm].	830
Stat. radius (SLR) [mm]	385
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
116 A6	1250	30		3,60	
	1120	40		3,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.