

TYRES

Product group	Tyres	
Item number	15711712	
Valid tyre size	7.50 - 16	
LI / SI / PR	111 J, 8 PR	
TL/TT	тт	
Brand	ВКТ	
Tread pattern	Sand King	





Notes and features

- The BKT Sand King has been specially developed for trailers in transport applications.
- Its block tread pattern provides excellent traction and optimum ground contact on sandy surfaces.



Technical Informations

Item number	15711712
EAN	8903094032457
Valid tyre size	7.50 - 16
LI / SI / PR	111 J, 8 PR
TL/TT	тт
Brand	BKT
Tread pattern	Sand King
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	18,72
Recommended rim size	5.50
Permitted rim size	6.00
Maximum air pressure [bar].	4,15
Section width (mm)	215
Outer diameter of tyre [mm].	820
Stat. radius (SLR) [mm]	378
Rolling circumference [mm].	2471
Tread depth (mm)	12,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
111 J	1090	100		4,11	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.