

TYRES

Product group	Tyres
Item number	15711715
Valid tyre size	12.5L - 16 SL
LI / SI / PR	128 D, 12 PR
TL/TT	ТТ
Brand	ВКТ
Tread pattern	Farm Implement I-1



Notes and features

- The BKT Farm Implement I-1 is a universal implement tyre for road and field applications as well as for soil tillage operations
- As a high-speed tyre, it has speed index D and is approved up to 65 km/h
- Thanks to its excellent flotation capabilities, it reduces soil compaction and protects soil and crops



Technical Informations

Item number	15711715
EAN	8903094006069
Valid tyre size	12.5L - 16 SL
LI / SI / PR	128 D, 12 PR
TL/TT	тт
Brand	BKT
Tread pattern	Farm Implement I-1
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	21,42
Recommended rim size	10
Maximum air pressure [bar].	3,60
Section width (mm)	310
Outer diameter of tyre [mm].	845
Stat. radius (SLR) [mm]	374
Rolling circumference [mm].	2476
Tread depth (mm)	9,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
128 D	1800	65		3,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.