

TYRES

Product group	Tyres
Item number	15711716
Valid tyre size	14L - 16.1 SL
LI / SI / PR	127 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	Pro Rib F2M



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Pro Rib F2M is a tyre designed for front-wheel use on smaller tractors in soil tillage applications.
- Especially suitable for all applications that require outstanding handling properties.
- Thanks to its high flotation capability, the tyre helps reduce soil compaction.

Technical Informations

Item number	15711716
EAN	8903094020485
Valid tyre size	14L - 16.1 SL
LI / SI / PR	127 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	Pro Rib F2M
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	46,34
Recommended rim size	W11C
Maximum air pressure [bar].	3,60
Section width (mm)	355
Outer diameter of tyre [mm].	980
Stat. radius (SLR) [mm]	453
Rolling circumference [mm].	2920
Tread depth (mm)	27,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
127 A8	1750	40		3,60	