

## TYRES

Product group	Tyres
Item number	15711722
Valid tyre size	4.00 - 16
LI / SI / PR	66 A8 / 78 A8, 4 PR
TL/TT	TT
Brand	BKT
Tread pattern	AS 504



Bohnenkamp  
Moving Professionals



## Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

## Technical Informations

Item number	15711722
EAN	8903094056576
Valid tyre size	4.00 - 16
LI / SI / PR	66 A8 / 78 A8, 4 PR
TL/TT	TT
Brand	BKT
Tread pattern	AS 504
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	5,15
Recommended rim size	3.00D
Permitted rim size	2.50
Maximum air pressure [bar].	2,80
Section width (mm)	110
Outer diameter of tyre [mm].	628
Stat. radius (SLR) [mm]	296
Dynamic radius [mm]	296
Rolling circumference [mm].	1935
Tread depth (mm)	16,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
66 A8	300	40	Drive Wheel	2,80	LLV
78 A8	425	40	Free Rolling	2,80	LLV