

TYRES

Product group	Tyres
Item number	15711726
Valid tyre size	10.0 / 75 - 15.3
LI / SI / PR	118 A8 / 130 A8, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	MP 567



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT MP 567 is a multi purpose tyre offering maximum flexibility.
- The tyre features good traction in all weathers.
- Suitable for on- and off-road use.
- The open tread pattern allows for efficient self-cleaning.
- Suitable for use on vehicles such as Unimogs, backhoe loaders, dumpers, etc.

Technical Informations

Item number	15711726
EAN	8903094057566
Valid tyre size	10.0 / 75 - 15.3
LI / SI / PR	118 A8 / 130 A8, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	MP 567
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	21,35
Recommended rim size	9.00
Permitted rim size	9.0
Maximum air pressure [bar].	5,50
Section width (mm)	258
Outer diameter of tyre [mm].	774
Stat. radius (SLR) [mm]	355
Rolling circumference [mm].	2310
Tread depth (mm)	21,5
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
118 A8	1320	40	Drive Wheel	5,50	LLV
130 A8	1900	40	Free Rolling	5,50	LLV